

In the specification:

Page 7, after line 1, insert:

The housing 10 extends in a longitudinal direction 42. The cooling conduit 30 of the cooling device is located in direct proximity to the at least one intake nozzle 20 and is separated from the housing 10 in a direction which is transverse to the longitudinal direction by means of an additional casing 38. The additional casing 38 is located between the cooling conduit 30 and the housing 10 in the transverse direction.

The cooling conduit 30 has a longitudinal direction which extends over an entire extension of the cooling conduit 30 in the same direction as the longitudinal direction 42 of the housing 10. The intake nozzles 20 and the cooling conduits 30 share a borderline 36 with each other.

An additional cooling conduit 40 is further provided. This is suppliable with air through the inlet openings 16, 18. The additional cooling conduit 40 is separated from the cooling conduit 30. The cooling conduit 40 in its entirety extends in a direction which is parallel to the longitudinal direction 42 of the housing 10.

The additional casing 38 is configured as an extension of the intake nozzle 20 in a longitudinal direction 44 of the intake nozzle 20. The longitudinal direction 44 of the intake nozzle 20 has the same direction as the longitudinal direction 42 of the housing.

The additional casing 38 is configured in a nonintegral manner with the housing 10 and in its entirety extends in a direction which is parallel to the longitudinal direction 42 of the housing 10. The additional casing 38 is configured so that it leads cooling air from the intake nozzle 20 to a motor housing 26.